

TER17

GENERAL CHARACTERISTICS

Wet / White Wet Inlay dimensions: 99 x 14 mm
—Antenna dimensions: 95 x 11 mm
 Standard pitch: 17,6 mm

Operating frequency: Global (860 - 960 MHz)
 Chip: IMPINJ Monza 700 series (750 / 730)
 EPC Memory: 96 / 128 bits auto serialized
 USER Memory: 32 / None bits
 TID Memory: 96 bit with 48 bit unique serial number

Inlay substrate material: PET
 Inlay-to-liner adhesive: SH3020 (Arconvert)
 Liner material: CC62 (Arconvert)
 Total thickness over chip: 170 microns

Standard web width: 110 mm
 Unwind direction: Label side out


RF Protocol: RAIN RFID / ISO-18000-63 and EPC-global Gen 2v2 compliant
 RoHS: EU Directive 2011/65 EU Compliant
 Quality assurance: 100% read tested with out-of-tolerance inlay marked
 Operating temperature: -40°C to 85°C

COMMON APPLICATIONS

Apparel and other retail item-level. Supply chain, inventory and logistics. Returnable Transport Units.


Minimum order quantity: 10,000 pcs. Average of units per roll: TBD

PERFORMANCE INDICATORS



Trace-ID's UHF RFID tag TER17 with IMPINJ M700 Chip series was developed to improve performance of its predecessor and suits RFID solutions for **Returnable Transport Units, supply chain, logistics, and inventories**. It's also appropriate for **retail item-level deployments** like apparel traceability.

MEASUREMENT AND FORMAT



All graphs are indicative; performance in real life applications may vary.

CARE AND HANDLING RFID inlays are sensitive to ESD. Observe standard practices to keep environmental static charge to a minimum. APPLICATIONS This product should be tested by the customer/user thoroughly under end use conditions to ensure the product meets the requirements. Trace-ID does not represent that this product is fit for any purpose or use. PRODUCT CHANGES Trace-ID reserves the right to modify, change, supplement or discontinue product offerings at any time without notice. © 2020 Trace-tech Id Solutions S.L. All rights reserved.