

# **BioMini Slim 3**

Ultra-slim FAP30 Authentication Scanner



BioMini Slim 3 is FAP30 certified fingerprint scanner featuring an array of cutting-edge technologies. Along with its 15mm slim optical sensor, BioMini Slim 3 features Suprema's proprietary Multi-dynamic Range(MDR) technology, FBI PIV/Mobile ID FAP30 compliance and Android device support. BioMini Slim 3 also provides developers more physical flexibility with its reduced form factor and the ultra-slim optical sensor ensures robust operation over time. BioMini Slim 3 provides new and advanced Live Finger Detection(LFD)technology by applying a machine learning method based AI(Artificial Intelligence) as an World-class Trained Inspector which can be upgradeable by BioMini SDK.



## BioMini Slim 3

Ultra-slim FAP30 Authentication Scanner

#### **FEATURES**



· World's thinnest FAP30 optical fingerprint scanner



- · FBI PIV and FBI Mobile ID FAP30 certificate
- · Image compression standard: WSQ



- · Capturing high-quality fingerprint images even when the finger is dry & wet.
- · Operates under direct sunlight up to 100,000 LUX



- · Live Fingerprint Detection(LFD) Technology
- Distinguishes fake fingerprints made from various materials including clay, rubber, silicon, glue, paper, film and more



- · Easy Integration
- $\operatorname{\mathsf{BioMini}}\nolimits\operatorname{\mathsf{SDK}}\nolimits$  for easy application development
- Android, MS Windows & Linux compatible
- Multi-threaded code design for multi-core CPU utilization

### **SPECIFICATIONS**

Sensor	Image Quality Standards	FBI PIV / FBI Mobile ID FAP30 compliant
	Live Finger Detection	0
	Sensor Type	Optical
	Resolution	500 ppi
	Gray Scale	256 level
	Platen Size (W x L mm)	21.5 x 26.5
	Sensing Area (W x H mm)	20.32 x 25.4
	Image Size (W x H pixels)	400 x 500
H/W	Interface	USB 2.0 High Speed
	Operating Temperature	-10 ~ 50°C
	Operating humidity	0 ~ 90% RH
	Ingress Protection	IP65 (Sensor Surface)
	Dimensions	83 x 45.9 x 20
	(W x L x H mm)	BM-Slim3: 67.5 x 36 x 15 (OEM)
	Weight	111g
S/W	Windows	Windows 7 or higher (32/64bit)
	Linux	Linux Kernel 3.x or higher
	Android Android 5.0 (Lollipop) and Above	Android 5.0 or higher (USB Host)
	Image Format	RAW, BMP, WSQ, ISO 19794-4
	Template Type	Suprema, ISO19794-2, ANSI-378
	LFD	0
Certification	CE	0
	FCC	0
	KC	0
	RoHS	0
	СВ	0
	IEC62471	0
	WEEE	0
	REACH	0
	WHQL	0



#### Suprema ID Inc.

#305~308, 3F, Building A, Tera Tower 2, 201 Songpa-daero, Songpa-gu, Seoul, Republic of Korea T +82 31 710 5629 E sales\_id@supremainc.com www.suprema-id.com